



GAS BURNER

C492A



Year 1
study

Features

- Flame Failure Device.
- Integral Fan with adjustable air volume control.
- Adjustable gas pressure.
- Push button Control Box with integrated fault diagnostic.
- Multibloc fuel control Valve.
- Ignitor and Burner Head.
- 2:1 turn down ratio
- hinged mounting for ease of fitting and removal.
- easy change burner nozzles for testing different fuels.

Description

An automatic package burner, comprising flame failure device, integral fan, control box, multibloc valve, igniter and burner head. The C492A is suitable for operation with Natural gas (Methane). Alternatively, it can be user-set to operate with bottled gases such as LPG (Liquefied Petroleum Gas) / Butane / Propane mixtures. It operates on heat rates up to 100kW approx. (depending on fuel). Automatic start sequence, involving a purge period, spark ignition, then fuel admission. Gas burner has ionisation probe flame detection systems which shut down the burner in the event of flame failure.

Related Laws/Applications

- Building services
- Mechanical Engineering
- Marine engineering
- Chemical engineering
- Mining engineering
- Environmental engineering
- Energy Conservation
- Industrial Research
- Vocational, Plant Maintenance
- Fuel Technology
- Thermodynamics

Learning capabilities

- Familiarisation of the adjustment and operation of a commercial Gas burner.
- Assessment of a burner
- Firing rate
- Turndown range
- Flame stability
- Flame shape
- Flame radiation
- Smoke emission
- Using either clean light boiler fuels, or natural gas or LPG
- The effect of air/fuel ratio on Combustion efficiency as measured by flue gas constituents and temperature.
- The effect of air/fuel ratio on Heat transfer
- The effect of air/fuel ratio on Energy balance
- Comparison of Flue Gas Analysis with theoretical predictions.
- Comparison of Oil and Gas Burners (With optional extra Burner)
- Comparative performance of different fuels or fuel additives.

Technical Specification

- Gas Burner: Package burner with integral fan and control box, and multibloc valve. Operates on natural gas (methane) or LPG gases at heat rates up to 100kW approx. (depending on fuel).

Essential Ancillaries

- C492/230/B
- (or C492/115/B)

Recommended Ancillaries

- C492B

What's in the Box?

- 1 x C492 Gas Burner
- 1 x Gas Pressure Test Gauge
- 1 x Gas Supply Connector Assembly
- 1 x Manometer
- 5m x LPG tubing
- 10m x PVC tubing
- Fittings
- Instruction manual
- Packing list
- Test sheet
- Wiring Diagram

You might also like

- C492B
- C492C
- C492D

Essential Services

- C492/230/B or C492/115/B

Ordering information

To order this product, please call PA Hilton quoting the following code: C492A

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS