



CAM and FOLLOWER APPARATUS HTM8



Year 1
study

Features

- Self-contained bench top unit
- Set of five cams supplied
- Set of two followers supplied
- Angular and linear displacement recorded
- Derive Velocity and Acceleration diagrams

Description

A vertical pillar contains the main spindle for each cam to be rotated, whilst a dial gauge has its anvil resting on the top edge of the cam. Each cam is mounted on a central shaft and is free to rotate about this shaft. The cams are rotated by hand.

The rise and fall displacement of the cam, as it rotates through 360°, is measured using the dial gauge. The angular position of the cam is shown on a protractor and a pointer. Cams and followers are easily changed and

graphs for the variety of cams can be created to compare the linear change with the rise and fall of the follower.

A set of cams are supplied as standard along with a set of followers which run on the perimeter of each cam. Each cam can be easily changed and the angular and dial gauge readings are clear.

Related laws

- Mechanisms
- Cams
- Followers
- Constant Speed
- Velocity Diagram
- Acceleration Diagram
- Linear displacement against rotation
- Simple Harmonic Motion

- Dwell
- Internal Combustion Engine
- Automatic Handling Machinery

Learning capabilities

- To determine a graph of follower displacement against angular rotation of the cam
- To derive the velocity and acceleration diagrams, and determine the maximum acceleration of the follower
- To assess the effect of different cams and followers
- To compare experimental and calculated results

Technical Specification

- Simple Harmonic Motion Cam: Rise/Fall 24mm
- Tangent Cam: Large radius 32mm; small radius 15mm
- Eccentric Cam: 10mm eccentricity
- Roller follower: Ø19mm
- Dial gauge: 25mm range, 0.01mm resolution
- Angular protractor scale with 360° range and 1° resolution

What's in the Box?

- 1 x HTM8 Assembly
- 1 x Simple Harmonic Motion Cam
- 1 x Uniform Motion Cam
- 1 x Constant Acceleration Cam
- 1 x Tangent Cam
- 1 x Eccentric Cam
- 1 x Dial Gauge
- Instruction manual
- Packing list
- Test sheet

Weights & Dimensions

- Weight: 6 kg
- Length: 250mm
- Width: 150mm
- Height: 540mm

Essential Services

- Sturdy Bench top

Operational Conditions

- Storage temperature: -10°C to +70°C
- Operating temperature range: +10°C to +50°C
- Operating relative humidity range: 0 to 95%, non condensing

Ordering information

To order this product, please call PA Hilton quoting the following code:
HTM8

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS