

## FLOW METER MODULE HB100K



1  
study

### Features

- Determines flow rate
- Utilises a graduated scale from 0-60l/min
- Accurate to between 5 and 60l/min

### Description

This Hydraulics Bench module allows students to determine the flow rate of any optional system that is attached to the base unit. The HB100K flow meter is of the variable area design. It connects to the base unit through the supplied piping and can accurately measure the flow rate between 5 and 60 l/min. This allows accurate results to be achieved when being used with any of the optional experimental units. To release the water in the meter, water can be drained back into the HB100 by using the tap on the inlet pipe.

### Learning capabilities

- Determination of flow rate with any attached HB system.
- The HB100K is essential for operation of certain modules. Please refer to individual specifications.

### Technical Specification

- Graduated scale from 0-60l/min
- Drain tap

### Essential Ancillaries

- HB100/230
- or
- HB100/115

### Recommended Ancillaries

- HB100C
- HB100D

### What's in the Box?

- Experimental module
- Link pipe assembly
- Blanking pipe

**Weights & Dimensions**

- Weight: 5 kg (Without water)
- Length: 520mm
- Width: 520mm
- Height: 840mm

**Essential Services**

- HB100/230
- or
- HB100/115

To order this product, please call PA Hilton quoting the following code:

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS