



## EFFICIENCY OF SCREW THREADS

### HTM6



#### Features

- Wall mounted apparatus
- Introduction to simple machines
- Determination of velocity ratio mechanical advantage and efficiency
- Comparative efficiency of square and Vee form threads
- Three thread forms provided with integral turntables and cords
- Calibrated weights set and hangers supplied

#### Description

Compact wall mounted apparatus to conduct experiments on the efficiencies of carrying screw thread forms. Three screw thread forms are supplied ('V' x 2 and square) each with an integral turntable mounted on the top side. Wrapped around the periphery of the turntable is a cord which allows the turntable to be rotated when loaded. Each thread has a mating nut with a profiled groove in its side. This groove locates onto a pin within the wall bracket assembly and stops the nut from rotating when the turntable and screw thread are rotated. Each nut and thread pairing are quickly and easily interchanged. The cord is run over the pulley and terminates to a load hanger. This hanger is described as the 'EFFORT' hanger. Another hanger is attached to the underside of the shaft of the screw thread and is described as the 'LOAD' hanger. Students vary the LOAD using the calibrated weights and obtain the respective EFFORT required to raise or lower the screw thread. From this the efficiencies can be obtained.

#### Learning capabilities

- Experimental determination of velocity ratio and comparison with calculated value
- Determination of variation with load of effort, friction and efficiency
- Limiting efficiency of the machine
- Comparison of relative efficiency of Vee and Square thread forms

#### Technical Specification

- Wall mounted apparatus to compare the efficiencies of square and 'V' form screw threads
- Torque applied to threads using turntable and cord
- The effort can be applied to raise or lower the load
- Load applied to screw thread and effort hanger can be changed

**What's in the Box?**

- 1 x HTM6 main assembly
- 1 x M16 x 3mm Pitch Thread complete with Brass Nut and Cord
- 1 x M16 x 3mm Pitch, V Thread complete with Brass Nut and Cord
- M16 x 2mm, V Thread complete with Brass Nut
- 1 x 100g hanger
- 1 x 10g hanger
- 1 x 5N hanger
- 1 x primary weight set including: 8 x 0.1N, 2 x 0.2N, 1 x 1N, 2 x 2N, 2 x 5N, 1 x 10N
- 1 x secondary weight set including: 1 x 20N, 4 x 50N
- 1 x hanger link
- 1 x 5m Cord

**Weights & Dimensions**

- Net dimensions: 320mm (H) x 230mm (W) x 240mm (D)
- Net weight (excluding weight set): 9Kg

**Operational Conditions**

- Storage temperature: -10°C to +70°C
- Operating temperature range: +10°C to +50°C
- Operating relative humidity range: 0 to 95%, non condensing

**Ordering information**

To order this product, please call PA Hilton quoting the following code:  
HTM6 - Efficiency of Screw Threads

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 5 YEARS